

Construction Products Regulation 2011: Declaration of Performance (DoP)

CPR Nr. 305/2011 (EU)

DoP Number: ZDP-EED-001-EU

CE Certificate of Conformity Number: ABB5007

- Unique identification code of the product-type: ZDL7260ESC Series Mortice Escape Lock
- Intended use or uses: Fire and smoke compartmentation doors, to fulfil self-closing requirements
- Name of manufacturer: ERA Home Security Ltd Trading as Zoo Hardware, Unit B, Dukes Drive, Kingmoor Park North, Cumbria, Carlisle, CA6 4SH
- **EU representative:** SchlegelGiesse, Giesse S.p.A., Via Tubertini G,1, 40054 Budrio, Bologna, 295136 Italy
- System of assessment product as set out in CPR, Annex V: System 1
- Harmonised standard: EN179: 2008
- Notified body: 2812 Element Materials Technology, Rotterdam B.V.

Declared Performance:

Essential Characteristic	Performance:	Harmonised Technical Specification:
Ability to Release	-Release function (<1 Sec): Pass	EN179: 2008
(For doors on	-Lever handle: Pass	
escape routes)	-Single door set: Pass	
	-Exposed edges and corners: Pass	
	-Lever handle installation: (X> 120mm, Z < 150mm) Pass	
	-Operating element projection: (W< 100mm) Pass	
	-Operating element face: (V> 18mm (Free End), U> 40mm,	
	W< 100mm, A< 30°: Pass	
	-Lever handle operating gap test rod: Pass	
	-Accessible gap: Pass	
	-Door free movement: Pass	
	-Top vertical bolt: Pass	
	-Keepers dimensions: Pass	
	-Outside access device: Pass	
	-Release forces: Pass	
1	-Security requirement: Pass (Grade 5)	

Continued on page 2





Declared Performance:

Essential Characteristic	Performance:	Harmonised Technical Specification:
Durability of ability to	-Corrosion resistance: Pass (Grade 4)	EN179: 2008
release against aging	-Temperature range: Pass	
and degradation (for	-Lubrication: (Every 20,000 cycles)	
doors on escape	-Re-engagement force: (<50 N) Pass	
routes	-Durability: Pass (Grade 7 – 200,000 cycles)	
	-Abuse resistance (Lever handle): Pass (500N, 1000N)	
	-Final examination: (Type A <70 N) Pass	
Self-closing ability C	-Re-engagement force: (<50 N) Pass	
(for fire/smoke doors	-Durability: Pass (Grade 7 – 200,000 cycles)	
on escape routes)	-Re-engagement force: (<50 N) Pass	
Resistance to fire E	-Suitability of emergency exit devices for use on fire	
(integrity) and I	resisting door sets and assemblies: Pass (Grade B)	
(insulation) (for		
fire/smoke doors on		
escape routes)		
Control of dangerous	The materials in the product/s do not contain or release	
substances	any dangerous substances in excess of the maximum	
	levels specified in existing European material	
	standards or any national regulations.	









Suitable accessories:

Model Number:	Description:	Suitable For Use on Fire Doors:
ZB030	Brass return to door lever handle set 19mm Ø, c/w screw on rose	
ZAA030SA	Aluminium return to door lever handle set, 19mm Ø, c/w screw on rose	•
ZAA080SA	Aluminium return to door lever handle set, 22mm Ø, c/w screw on rose	•
ZCS2030SS	Stainless Steel grade 201 return to door lever handle set, 19mm Ø, c/w push on rose	•
ZCS2080SS	Stainless Steel grade 201 return to door lever handle set, 22mm Ø, c/w push on rose	•
ZCS030SS	Stainless Steel grade 304 return to door lever handle set, 19mm Ø, c/w push on rose	•
ZCS2080SS	Stainless Steel grade 304 return to door lever handle set, 22mm Ø, c/w push on rose	•
ZPS030SS	Stainless Steel grade 304 return to door lever handle set, 19mm Ø, c/w push on rose	•
ZPS080SS	Stainless Steel grade 304 return to door lever handle set, 22mm Ø, c/w push on rose	•
ZG4S030	Stainless Steel grade 304 return to door lever handle set, 19mm Ø, c/w cast push on rose	•
VS030	Stainless Steel grade 304 return to door lever handle set, 19mm Ø, c/w 4mm push on rose	
VS070	Stainless Steel grade 304 return to door lever handle set, 19mm Ø, c/w 4mm push on rose	•
VS080	Stainless Steel grade 304 return to door lever handle set, 21mm Ø, c/w 4mm push on rose	Ø
ZSP12	Split spindle	Ø

Signed for and on behalf of the manufacturer by:

Ben Penson

Technical, Innovation and Development Director

ERA Home Security Ltd

Date of First Issue: 16/8/2022

Updated: 30/9/2022